## **SMB Bearings**

## Radial Ball Bearing

## Part Number: CCZR-R8



(for illustration only)

	<b>&gt;</b>	0.2500"	◆	
			_	
<b>↑</b>	ſ		<b>→</b>	0.4mm (min.)
			<u> </u>	
			_	
1				
1.1250"				
0.50	00"			
			_	
	r		1	
<b>↓</b>			J	

Material (rings & balls)	Zirconium dioxide (ZrO2)		
Material (cage)	Full complement, PEEK or PTFE		
Closures	None		
Load rating (stat)	183 Kgf		
Load rating (dyn)	391 Kgf		
Speed Limit *	6,400 rpm		
Standard Lubrication **	None		

<sup>\*</sup> with adequate lubrication

These bearings comply with EU ROHS and REACH regulations.

RADIAL PLAY	C2	CN	С3	C4
(microns)	0 - 9	3 - 18	11 - 25	18 - 33

TOLERANCE	P0		
Bore Deviation	+0 / -0.008mm		
OD Deviation	+0 / -0.009mm		
Width Deviation	+0 / -0.120mm		

SMB Bearings take no responsibilty for any errors or omissions in this data sheet. We reserve the right to change specifications without prior notice. We recommend that adequate testing is carried out on products before they are determined as suitable for an application.

<sup>\*\*</sup> may vary