
## **SMB Bearings**

## Part Number: CCZR-6905



## **Radial Ball Bearing**



(for illustration only)

| Material<br>(rings & balls) | Zirconium dioxide<br>(ZrO2)      |  |
|-----------------------------|----------------------------------|--|
| Material (cage)             | Full complement,<br>PEEK or PTFE |  |
| Closures                    | None                             |  |
| Load rating (stat)          | 335 Kgf                          |  |
| Load rating (dyn)           | 517 Kgf                          |  |
| Speed Limit *               | 3,600 rpm                        |  |
| Standard<br>Lubrication **  | None                             |  |

\* with adequate lubrication

\*\* may vary

These bearings comply with EU ROHS and REACH regulations.

| RADIAL PLAY | C2     | CN     | C3      | C4      |
|-------------|--------|--------|---------|---------|
| (microns)   | 1 - 11 | 5 - 20 | 13 - 28 | 23 - 41 |

| TOLERANCE       | PO            |
|-----------------|---------------|
| Bore Deviation  | +0 / -0.010mm |
| OD Deviation    | +0 / -0.011mm |
| Width Deviation | +0 / -0.120mm |

SMB Bearings take no responsibility for any errors or omissions in this data sheet. We reserve the right to change specifications without prior notice. We recommend that adequate testing is carried out on products before they are determined as suitable for an application.